

Product Discontinuation Notices

RFID Systems


Issue Date
December 1, 2014

No. 2014077CE

Discontinuation Notice of Handy Terminal model V680-A-7527S-G3 series.

Product Discontinuation

Handy Terminal

 Model V680-A-7527S-G3-EG
Model V680-A-7527S-G3-EG-S
Model V680-A-WA3006
Model V680-A-WA6197



Recommended Replacement

Handy Terminal

Model V680-A-7527S-G4-EG
Model V680-A-7527S-G4-EG-S
Model V680-A-WA3025/WA3010
Model V680-A-WA6180
(Release on March 2015)

[Discontinuation date]

The end of March, 2015

[Caution on recommended replacement]

There is no change as follows ;

- The brand of these products is MOTOROLA SOLUTIONS.
- The software (Easy Access and CB Access) is preinstalled.
- The following products are compatible with V680-A-7527S-G4 series.
 - model V680-A-CA1053
 - model V680-A-WA4003

[Difference from discontinued product]

Recommended replacement Model	Body Color	Dimen-sions	Wire connection	Mounting Dimensions	Charact-eristics	Operation ratings	Operation methods
V680-A-7527S-G4 series	*	*	**	-	*	-	*

** : Compatible

* : The change is a little/Almost compatible

-- : Not compatible

- : No corresponding specification




[Product Discontinuation and recommended replacement]

Product discontinuation	Recommended replacement
V680-A-7527S-G3-EG	V680-A-7527S-G4-EG
V680-A-7527S-G3-EG-S	V680-A-7527S-G4-EG-S
V680-A-WA3006	V680-A-WA3025
	V680-A-WA3010
V680-A-WA6197	V680-A-WA6180

[Body color]

<p>Product discontinuation Model V680-A-7527S-G3 series</p>	<p>Recommendable replacement Model V680-A-7527S-G4 series</p>
<div style="text-align: center;">  </div> <p data-bbox="229 1021 683 1084">The picture is Handy Terminal only. (The serial end-cap is not connected.)</p>	<div style="text-align: center;">  </div> <p data-bbox="911 1021 1364 1084">The picture is Handy Terminal only. (The serial end-cap is not connected.)</p>

[Wire connection]

<p>Product discontinuation Model V680-A-7527S-G3 series</p>	<p>Recommendable replacement Model V680-A-7527S-G4 series</p>
<div style="text-align: center;"> <p data-bbox="395 1305 512 1335">Top View</p>  </div> <div style="text-align: center;"> <p data-bbox="379 1581 528 1610">Bottom View</p>  </div>	<div style="text-align: center;"> <p data-bbox="1082 1305 1198 1335">Top View</p>  </div> <p data-bbox="1023 1659 1257 1688">Same as on the left</p>

[Dimensions]

Product discontinuation Model V680-A-7527S-G3 series	Recommendable replacement Model V680-A-7527S-G4 series
Height : 200 mm Width : 100 mm Depth : 42 mm (The serial end-cap is not connected.)	Same as on the left

[Characteristics]

Item	Product discontinuation Model V680-A-7527S-G3 series	Recommendable replacement Model V680-A-7527S-G4 series
OS	Windows CE 5.0	Windows Embedded CE 6.0
Processor	Xscale PXA270 624MHz	Sitare AM37x ARM Cortex-A8 1GHz
Display	FullVGA 480×640 3.7 inch	FullVGA/QVGA 640×480 3.7 inch
Battery	Standard battery 3.7V 3300mA/h	Standard battery 3.7V 2760mA/h
Ambient operating temperature	-20°C to +50°C	
Ambient storage temperature	-40°C to +60°C	
Ambient operating humidity	5% to 95%	
Degree of protection	IP65, IEC60529	
ESD	+/- 4 kVdc contacts, +/- 8 kVdc air discharge	+/- 8 kVdc contacts, +/- 15 kVdc air discharge

Specifications and prices in this product news are as of the issue date and are subject to change without notice. Only main changes in specifications are described in this document. Please be sure to read the relevant catalogs, datasheets, product specifications, instructions, and manuals for precautions and necessary information when using products.